

## Aggregation Switch

### HSP-IO-24GE4XS-C3PA+

#### 24-Port PoE+ L3 Managed Switch



### Overview

- Fully Managed L3 Switch with wire speed Non-Blocking Architecture
- All Gigabit Ethernet Access Ports with 10G Uplinks in a fixed 1U configuration
- 24x10/100/1000 Base-T Access ports
- 4x1/10G SFP+ Uplink Ports that allow termination on either fiber or copper based on SFP module
- Powerful WebGUI with industry standard Command Line Interface
- Upto 128 Gbps Switching capacity and up to 95.232 MPPS of full duplex throughput
- Comply with Energy Efficient Ethernet Standards (802.3az)
- Suitable as Access or Aggregation Switch in Enterprise/ Campus/ Telco Environment

### Switch Ports

- 24x10/100/1000 Base-T Gigabit Access Ports
- 4x1/10G SFP+ Uplink Ports (MSA Compliant)
- One Serial Console Port and One Out-of-Band Management Port
- Link, Activity, Speed, PoE Status LEDs
- System status LED and onboard RESET button

### Industry Standard Management with Automation

- **Management Interfaces:** CLI and WebGUI
- **Protocol Support:** Dual Stack (IPv4/IPv6), Telnet, SSHv2, SNMP v1/v2/v3, SMTP
- **Monitoring & Analytics:** RMON, sFlow, Port Mirroring, L2 and L3 Traceroute
- **Time Services:** NTP and Secure NTP
- **IP Services:** DHCP Server, Relay, and Client
- **File Transfer & Provisioning:** FTP, TFTP, SCP, SFTP, Zero Touch Provisioning
- **Diagnostics & Resiliency:** Time Domain Reflectometry, Dying Gasp

# HSP-IO-24GE4XS-C3PA+

## KEY FEATURE HIGHLIGHTS



### Rich L2 Features

- **VLANS:** Support up to 4094 VLAN IDs, Voice VLAN, IP-subnet VLAN, Protocol-based VLAN, Private VLAN, MAC-based VLAN, GVRP/MVRP for dynamic VLAN registration
- **Loop Avoidance & Resiliency:** STP (802.1D), RSTP (802.1w), MSTP (802.1s); STP Root and Edge Port Protection; ERPS (ITU-T G.8032); UDLD (Unidirectional Link Detection)
- **Multicast:** IGMP v1/v2/v3 Snooping, IGMP Filtering, IGMP Proxy, IGMP Querier, MLD Snooping and MVR (Multicast VLAN Registration)
- LACP-based LAG, Static LAG with load sharing and active-passive policies
- IEEE 802.1Q VLAN Tagging, QinQ (Port-based)
- **QoS:** Up to eight priority queues, Rate Limiting/Policing, Shaping (SP, WRR), Multi-Field (802.1p/DSCP) Classification and Remarking
- LLDP and LLDP-MED for end-point/VoIP device discovery
- **MAC Table:** 32K entries, Jumbo MTU: 10240 Bytes

### L3 Features

- IPv4 and IPv6 Static Routing
- RIP v1/v2 L3 Dynamic Routing
- OSPFv2/v3 L3 Dynamic Routing
- Inter-VLAN Routing
- IPv4/IPv6 Dual Stack

### PoE Features

- PoE Budget - 370W
- Per port PoE configuration and scheduling
- Auto PoE Check and reboot if device does not respond
- Persistent PoE and Power Delay (to let the device boot)

### Security Features

- L2/L3/L4 ACL with extended features
- 802.1X Port Security with RADIUS Accounting & Dynamic VLAN Assignment, Dynamic/Downloadable ACLs
- **AAA Support:** TACACS+, RADIUS and RADSec
- DHCP snooping, Dynamic ARP Inspection, DHCPv6 Guard
- Port Security, Sticky MAC, IP-MAC Binding
- PKI Key, Certificate, SSL IPv4/IPv6, IPv6 Source Guard
- Storm Control - Broadcast, Multicast and Unknown Unicast

### Advanced Features

- IEEE 802.3ah Link-level OAM
- IEEE 802.1ag Ethernet CFM (ITU-T Y.1731 Performance Monitoring)

### Switching / Forwarding Capacity

**Switching Capacity** 128 Gbps

**Forwarding Capacity** 95.232 MPPS

### Design Parameters

- Operating Temperature: -5°C to 50°C
- 1U fixed configuration
- Humidity: 5% to 95% non-condensing
- Altitude: 3000 Meters (10,000 Feet)
- Dimension (WxHxD): 442 x 44 x 211 mm

### Power Supply Options

- Integrated Single AC Power Supply (100-240 VAC)

# HSP-IO-24GE4XS-C3PA+

## KEY FEATURE HIGHLIGHTS



### Compliance & Certifications

<b>EMI/EMC (TEC)</b>	IEC 61000-4
<b>EMI/EMC (CE)</b>	EN55032 / EN55024
<b>FCC Compliance</b>	FCC Part-B
<b>Safety (CE)</b>	EN62368-1
<b>Reliability Test</b>	QM333 Cyclic
<b>Environmental Tests</b>	IEC 60068-2
<b>ESS Tests</b>	IEC 60068-2 (Vibration, Shock, Drop, Bump, High Altitude)
<b>MTCTE (India)</b>	Mandatory Testing & Certification of Telecom Equipment
<b>Trusted Portal</b>	Country-specific security/trust compliance
<b>RoHS</b>	Restriction of Hazardous Substances
<b>IPv6 Logo</b>	IPv6 Ready Logo Certification (Phase-2 Gold)

### Ordering Information

Model No.	Description
<b>HSP-IO-24GE4XS-C3PA+</b>	IO, 24-Port, PoE+, L3 Managed Switch, 4x1/10G SFP+ Uplinks, Single AC Power Supply
<b>HSP-IO-Cable-AC-IN</b>	AC Power Cable, 1.5M (India Plug)

**Disclaimer:** HFCL, IO by HFCL, and their respective logos are trademarks and/or registered trademarks of HFCL Limited. HFCL Limited assumes no responsibility for any inaccuracies in this document and reserves the right to revise or transfer this document without notice. All other trademarks, service marks, registered marks, or registered service marks mentioned herein are the property of their respective owners.

Last Updated September 2025



**Email:** [iosupport@hfcl.com](mailto:iosupport@hfcl.com)

**Website:** [hfcl.com](http://hfcl.com) | [io.hfcl.com](http://io.hfcl.com)

**Office:** 8, Commercial Complex, Masjid Moth, Greater Kailash II, New Delhi 110048