

Industrial Switch

HSP-IO-8GE2S-I2PDH

8-Port PoE+ L2 Managed Industrial Switch
(2x1G SFP and 2x1G RJ45 Uplinks)



Overview

- Fully Managed L2 Switch with wire speed Non-Blocking Architecture
- All Gigabit Ethernet Ports in a fixed configuration
- Four 1G PoE+ Capable Access ports
- Upto 24 Gbps Switching capacity and up to 12 Gbps of Full-Duplex Throughput
- Four 1G Uplink Ports that allow termination of both fiber and copper simultaneously
- Dual Redundant Power supply for high availability
- Rugged Design with DIN rail mount suitable for outdoor applications
- Suitable in an enterprise / telco / campus environments to connect end PoE clients like Wi-Fi AP, CCTV, P2P, P2MP, IoT etc.

Switch Ports

- 8x10/100/1000M Base-T Gigabit Access Ports with PoE+ support.
- 2x10/100/1000M Base-T + 2x1G SFP Gigabit Uplink Ports with the flexibility to terminate the connection on copper as well as fiber simultaneously.
- One Serial Console Port
- Link / Speed / LED Status on all ports
- System status LED & onboard RESET button

Industry Standard Management with Automation

- CLI and GUI (with NMS Server)
- Dual Stack (IPv4 and IPv6) Management
- Telnet, SSHv2 and SNMP v1/v2/v3 support
- NTP, FTP, TFTP, SCP, SFTP, Port Mirroring, Traceroute
- DHCP Client*
- Built-in Event Policy / Scheduler Framework for Automation
- Zero Touch Provisioning

*Contact sales representative for use case

HSP-IO-8GE2S-I2PDH

KEY FEATURE HIGHLIGHTS



Rich L2 Features

- Support 4094 VLAN IDs, 16K MAC Table, Voice VLAN
- L2 Loop Avoidance – STP/RSTP, MSTP, ERPS, STP Root and Edge Port Protection
- Multicast - IGMP v1/v2/v3 Snooping, IGMP filtering, IGMP proxy
- LACP based LAG and Static LAG with Traffic load share and active –standby policies
- Static Routing & Inter-VLAN Routing, Dual Stack and IPv6 Compliant
- 802.1q and QinQ (Port based and Selective), MVRP
- QoS – Up to eight priority queues, Rate Limiting/Policing, CIR/EIR, Shaping (SPQ / WRR/ WFQ), Multi-Field (802.1p / DSCP) Classification and Remarking
- LLDP / LLDP MED to identify end points, IP Phones etc.
- Jumbo MTU upto 9198 Bytes

Certifications

- Environment: IEC 60068-2, QM-333, RoHS
- EMI/EMC: EN 55024, EN 55032, CISPR 24, CISPR 32, IEC 61000-4
- Safety: EN 62368-1, IEC 62695-11-10, IEC 60320-1
- Software: IPV6 Ready Logo Certified

Security Features

- L2/L3/L4 ACL
- 802.1X Port Security with RADIUS CoA, dACL, Accounting & Dynamic VLAN Assignment
- TACACS+ / RADIUS AAA
- DHCP snooping
- MAC-IP Anti spoofing, MAC Address Notification
- Inherent DoS Attack Prevention
- Storm Control - Broadcast, Multicast and Unknown Unicast

Switching / Forwarding Capacity

Switching Capacity 24 Gbps

Forwarding Capacity 17.86 MPPS

Design Parameters

- Operating Temperature: -40°C to 75°C
- Rugged Design with DIN Rail Mount as well as Rack Mount options

Power Supply Options

- Dual DC Power Supplies

Ordering Information

Model No.	Description
HSP-IO-8GE2S-I2PDH	IO, 8-Port PoE+ L2 Managed Industrial Switch with 2x1G SFP and 2x1G RJ45 Uplinks and Dual DC Power Supplies

Disclaimer: HFCL, IO by HFCL, and their respective logos are trademarks and/or registered trademarks of HFCL Limited. HFCL Limited assumes no responsibility for any inaccuracies in this document and reserves the right to revise or transfer this document without notice. All other trademarks, service marks, registered marks, or registered service marks mentioned herein are the property of their respective owners.

Last Updated July 12, 2024



Email: iosupport@hfcl.com

Website: hfcl.com | io.hfcl.com

Office: 8, Commercial Complex, Masjid Moth, Greater Kailash II, New Delhi 110048